



# SM1006

## Creep Machine

**Bench-mounted machine which demonstrates the phenomenon of creep under different conditions and in different materials**

Works with  
**VDAS**<sup>®</sup>



Screenshot of the optional VDAS<sup>®</sup> software

- Ideal for student use and classroom demonstrations
- Demonstrates the three phases of creep
- Demonstrates effect of temperature on creep
- Compact and easily stored
- Supplied with weights and test specimens
- Inexpensive specimens readily available in lead and plastics
- Completely self-contained – needs no other parts

- TecEquipment Ltd, Bonsall Street, Long Eaton, Nottingham NG10 2AN, UK
- **T** +44 115 972 2611 • **F** +44 115 973 1520 • **E** info@tecequipment.com • **W** www.tecequipment.com
- An ISO 9001 certified company
- VDAS is a registered trademark of TecEquipment Ltd

# SM1006

## Creep Machine

### Description

This simple machine uses specimens of lead and different plastics which creep significantly at room temperature and under low loads.

Its main part is a simple lever (load beam) with a mechanical advantage of 8:1. The load beam gives a steady and uniform tensile load. A digital indicator measures the extension (creep) of the specimen under load. To ensure correct loading of the specimen, the load beam has a ball-bearing pivot.

To apply a load, students add weights to a weight hanger and measure time and the creep. For effect-of-temperature tests, the student freezes or heats a cool-pack and places it next to the specimen. They then fit the transparent enclosure to preserve the temperature around the specimen during the test.

Students may record and plot results by hand, using a timer (not supplied) and the readings from the digital indicator and thermometer. Alternatively, the student can use TecEquipment's optional Versatile Data Acquisition System (VDAS®) to capture the data, plot charts and export data.

A user guide is supplied with the Creep Machine. The guide includes full details of the equipment, detailed experiment procedures, theory and results.

For quick and reliable tests, TecEquipment can supply VDAS® which gives accurate real-time data capture, monitoring and display, calculation and charting of all important readings on a computer (computer not included).

For connection to VDAS® the Creep Machine includes a thermocouple with in-line transmitter, and a lead to connect the digital indicator to VDAS®.

### Standard Features

- Supplied with comprehensive user guide
- Five-year warranty
- Manufactured in accordance with the latest European Union directives

### Recommended Ancillaries

- Bench-mounted version of the Versatile Data Acquisition System (VDAS-B)
- Extra specimens:
  - CP1010 Lead to BS1178 (1969)
  - CP1020 Polypropylene
  - CP1025 Nylon 66 unfilled
  - CP1030 Unplasticised PVC

### Experiments

An extensive range of experiments may be carried out with this apparatus, including:

- The normal breaking load of a specimen over a fixed time
- Relationship between breaking load and time for lead specimens
- Time extension curves to show the three phases of creep (primary, secondary and tertiary)
- The effect of temperature on the creep rate of specimens
- Creep recovery

### Essential Services

None needed for ambient temperature tests. For 'effect of temperature tests', the cool pack must to be frozen in the ice making compartment of a refrigerator and heated in a pan of hot water.

*Bench space needed:*  
570 mm x 220 mm

### Operating Conditions

*Operating environment:*  
Laboratory

*Storage temperature range:*  
-25°C to +55°C (when packed for transport)

*Operating temperature range:*  
+5°C to +40°C

*Operating relative humidity range:*  
80% at temperatures < 31°C decreasing linearly to 50% at 40°C

### Sound Levels

Less than 70 dB(A)

### Specifications

*Dimensions:* 570 mm x 430 mm x 220 mm

*Nett weight:* 7.5 kg

*Approximate packed volume and weight:* 0.1 m<sup>3</sup>; 15 kg

*Temperature:* Displayed by laboratory-standard thermometer or thermocouple (SM1000CK) and VDAS®

*Creep:* Measured by digital indicator, with output for VDAS®

*Specimens (supplied):*  
10 x CP1010 Lead  
10 x CP1020 Polypropylene

*Test weights (supplied):*  
3 x 500 g  
2 x 200 g  
1 x 100 g

- TecEquipment Ltd, Bonsall Street, Long Eaton, Nottingham NG10 2AN, UK
- **T** +44 115 972 2611 • **F** +44 115 973 1520 • **E** info@tecequipment.com • **W** www.tecequipment.com
- An ISO 9001 certified company
- VDAS is a registered trademark of TecEquipment Ltd

*tradition.*

*innovation.*

*integration.*

**infoWERK** is a leading expert in the development of eLearning courseware, learning system solutions, teaching and AV equipment.

**Furthermore infoWERK is the representative and system integrator of "TecQuipment".**

**TecQuipment** is one of the global leaders in technical teaching equipment for engineering. If you are interested in one of TecQuipment's products feel free to contact us at:



**infoWERK Medien & Technik GmbH**

**Martinsbühel 6 / A-6170 Zirl / Austria**

Phone: +43 (0) 5238 52099-0 / Fax: +43 (0) 5238 52099-40

E-Mail: [info@infowerk.at](mailto:info@infowerk.at) / Website: [infowerk.at](http://infowerk.at)

**Otto-Dürr-Straße 25**

**D-70435 Stuttgart, Zuffenhausen/ Germany**

Phone: +49 (0) 711 342471-0 / Fax: +49 (0) 711 342471-11

E-Mail: [info@de.infowerk.at](mailto:info@de.infowerk.at) / Website: [infowerk.at](http://infowerk.at)