



Thermodynamics

TD300a**Exhaust Gas Calorimeter**

For use with TecEquipment's Regenerative Engine Test Set (TD300) to measure the heat content of engine exhaust gases

Works with
VDAS[®]



- Safely and effectively measures the heat content of TecEquipment test engine exhaust gases
- For use with TecEquipment's Regenerative Engine Test Set (TD300) and Test Engines (TD301 and TD302)
- Specially designed for educational use
- Wide range of investigations possible
- Uses electronic transducers and a digital display for ease of use and accuracy
- Separate instrumentation unit conveniently mounts on test set console frame
- Fully compatible with TecEquipment's Versatile Data Acquisition System (VDAS[®]) and software

- TecEquipment Ltd, Bonsall Street, Long Eaton, Nottingham NG10 2AN, UK
- **T** +44 115 972 2611 • **F** +44 115 973 1520 • **E** info@tecquipment.com • **W** www.tecquipment.com
- An ISO 9001 certified company
- VDAS is a registered trademark of TecEquipment Ltd

TD300a

Exhaust Gas Calorimeter

Description

An exhaust gas calorimeter for use with TecEquipment's Regenerative Engine Test Set (TD300). The equipment measures the heat content of exhaust gases and enables students to determine the energy lost to exhaust in the energy balance for single-cylinder, four-stroke petrol (TD301) and diesel (TD302) engines. The engines are separately available.

The main components of the Exhaust Gas Calorimeter are:

- Gas-to-water shell and multi-tube heat exchanger
- Control valve
- Instrumentation unit

The heat exchanger is mounted on a sturdy base plate. Exhaust gases from the test engine mounted on the test set flow through the tubes. A jacket of constantly flowing cooling water surrounds the tubes, and the heat content of the gases is assessed by measuring the cooling water flow rate and the inlet and outlet temperatures.

A hand-operated valve, which mounts on the control console of the test set, controls the flow of cooling water through the heat-exchanger jacket. Thermocouples measure the temperature of gas and water at the inlet and outlet. A turbine flow meter measures the flow rate. For safety, the heat exchanger also includes a pressure-relief valve in case insufficient cooling water is flowing.

The instrumentation consists of a digital, four-channel temperature and flow display unit. This unit mounts on the instrumentation rail of the test set console frame and allows easy and accurate display and monitoring of data. In addition, the Exhaust Gas Calorimeter is fully compatible with TecEquipment's Versatile Data Acquisition System (VDAS® available separately).

VDAS® enables accurate real-time data capture, monitoring and display, calculation and charting of all relevant parameters on a computer, (computer not included) making tests quick and reliable.

Standard Features

- Supplied with comprehensive user guide
- Five-year warranty
- Made in accordance with the latest European Union directives

Experiments

When used with TecEquipment's Regenerative Engine Test Set (TD300), the Exhaust Gas Calorimeter enables students to assess the heat lost to exhaust in the energy balance for single-cylinder four-stroke petrol (TD301) and diesel (TD302) engines.

Ancillary For:

Regenerative Engine Test Set (TD300)

Essential Services

Water supply and Drain:

Approximately 10 litres per minute at 1 bar minimum

Electrical supply:

Single-phase a.c. 90 to 240 V, 50/60 Hz

Operating Conditions

Operating environment:

Well ventilated laboratory

Storage temperature range:

-25°C to +55°C (when packed for transport)

Operating temperature range:

+5°C to +40°C

Operating relative humidity range:

80% at temperatures < 31°C decreasing linearly to 50% at 40°C

Specification

Nett Dimensions and weights:

- Calorimeter:
length 1200 mm x depth 500 mm x height 800 mm and 30 kg
- Temperature and flow display unit:
190 mm x depth 130 mm x height 450 mm and 4 kg

Approximate Packed Dimensions:

0.8 m³ and 50 kg

Heat exchanger:

Stainless steel shell and multi-tube with pressure-relief valve

Temperature measurement:

Thermocouples with digital display

Flow measurement:

Turbine flow meter with digital display

Flow control:

Hand-operated valve

- TecEquipment Ltd, Bonsall Street, Long Eaton, Nottingham NG10 2AN, UK
- **T** +44 115 972 2611 • **F** +44 115 973 1520 • **E** info@tecquipment.com • **W** www.tecquipment.com
- An ISO 9001 certified company
- VDAS is a registered trademark of TecEquipment Ltd



tradition.

innovation.

integration.

infoWERK is a leading expert in the development of eLearning courseware, learning system solutions, teaching and AV equipment.

Furthermore infoWERK is the representative and system integrator of "TecQuipment".

TecQuipment is one of the global leaders in technical teaching equipment for engineering. If you are interested in one of TecQuipment's products feel free to contact us at:



infoWERK Medien & Technik GmbH

Martinsbühel 6 / A-6170 Zirl / Austria

Phone: +43 (0) 5238 52099-0 / Fax: +43 (0) 5238 52099-40

E-Mail: info@infowerk.at / Website: infowerk.at

Otto-Dürr-Straße 25

D-70435 Stuttgart, Zuffenhausen/ Germany

Phone: +49 (0) 711 342471-0 / Fax: +49 (0) 711 342471-11

E-Mail: info@de.infowerk.at / Website: infowerk.at