



**TM1016****Free and Forced Vibrations**

***Investigates the free and forced vibrations of a rigid beam with a spring, and a simply supported beam***

Works with  
**VDAS<sup>®</sup>**



Screenshot of the VDAS<sup>®</sup> software

- Quick and easy to set up bench-top unit to demonstrate free and forced vibrations – designed for teaching
- Two different vibration systems in one self-contained unit – a ‘rigid’ beam with a spring, and a pinned-pinned (simply supported) ‘flexible’ beam
- Non-contacting displacement sensor – for frictionless measurements
- High-quality servomotor ‘exciter’ turns an offset mass – for forced vibrations at a constant speed
- Offset mass position sensor - to show the phase relationship between applied force and displacement
- Built-in accelerometer for comparison of derived and measured acceleration waveforms
- Includes a variable-area dashpot damper, using non-toxic, stable-viscosity fluid – for a range of damping coefficients
- Works with TecEquipment’s VDAS<sup>®</sup> (mkII) for real-time display of the vibrations

- TecEquipment Ltd, Bonsall Street, Long Eaton, Nottingham NG10 2AN, UK
- **T** +44 115 972 2611 • **F** +44 115 973 1520 • **E** info@tecquipment.com • **W** www.tecquipment.com
- An ISO 9001 certified company
- VDAS is a registered trademark of TecEquipment Ltd

# TM1016

## Free and Forced Vibrations

### Description

A bench-top unit to demonstrate free and forced vibrations of two mass-beam systems:

1. A 'rigid' beam with a pivot at one end and a spring at the other – the spring provides the elasticity
2. A 'flexible' pinned – pinned beam with a pivot at one end and a roller pivot at the other – the beam itself provides the elasticity

A rigid and heavy steel frame holds the systems. The frame has a low natural frequency, so the vibrations of the systems do not affect it. The frame has two sections: an experiment 'window' to the right and a control panel to the left. The experiment window contains the beam, spring and other parts used in the experiments.

TecEquipment carefully designed the equipment so that all experiments use the same beam. This gives a simple and quick system set up and changeover time. The beam is of high-grade ground steel, and the pivots use high-quality ball races for lowest friction and incidental damping.

Students may vibrate the systems manually. They may also force the vibrations using a high-quality variable speed servomotor driving a rotating offset mass - forming an 'exciter'. The servomotor has its own encoder and advanced controller for accurate speed regulation. This gives minimal cyclical variation due to inertial load variations.

A non-contacting sensor measures beam displacement. The sensor has no physical contact with the oscillating system, for negligible damping.

An accelerometer built into the exciter assembly works to show the phase relationship between beam displacement and acceleration. It also helps to compare measured acceleration with that derived from the displacement using the software.

The unit includes a variable-area viscous dashpot damper, for use with a non-toxic fluid (supplied) of stable viscosity. This ensures repeatable results over a range of ambient temperatures.

An encoder linked to the rotating exciter mass measures its dynamic position. This helps to measure the relationship between the applied force and the position of the beam, showing phase lag with different damping values.

TecEquipment include a vibration absorber with the equipment. When fixed to the beam it adds a second degree of freedom to the complete system. This demonstrates the typical behaviour of a 2 degree of freedom (2DOF) system. Students learn how to 'tune' the vibration absorber to eliminate the oscillations of the main beam - a special case of a 2DOF system and an alternative method to damping.

To help store small parts and tools, TecEquipment supply a storage tray with the equipment.

The control panel houses the servomotor controller and manual controls, alongside a digital display of the motor speed in units of  $\text{rev.min}^{-1}$ ,  $\text{rad.s}^{-1}$  and frequency in Hz. It also provides outputs of the displacement, acceleration, encoder (offset mass) position, and motor speed. These outputs are calibrated and scaled to work directly with TecEquipment's VDAS® (mkII) system.


The output signals connect to the VDAS® interface which converts them for connection to a suitable PC (not supplied).

The VDAS® (mkII) software includes functions to display live plots of first and second derivatives, to show velocity and acceleration waveforms based on the displacement signal. Advanced features of the software allow signal smoothing, reference plots and a tool to help measure the free vibration damping coefficient.

TecEquipment have specifically designed the TM1016 to work with VDAS. However, the sensor and trigger outputs may be connected to your own data acquisition system or oscilloscope if desired.

### Standard Features

- Supplied with comprehensive user guide
- Five-year warranty
- Manufactured in accordance with the latest European Union directives



VDAS software showing plot of damped oscillation

- TecEquipment Ltd, Bonsall Street, Long Eaton, Nottingham NG10 2AN, UK
- T +44 115 972 2611 • F +44 115 973 1520 • E info@tecequipment.com • W www.tecequipment.com
- An ISO 9001 certified company
- VDAS is a registered trademark of TecEquipment Ltd

# TM1016

## Free and Forced Vibrations

### Experiments

- Free and forced vibrations of a rigid beam and spring
- Free and forced vibrations of a flexible pinned–pinned (simply supported) beam
- Using Rayleigh’s approximation to predict vibration frequency
- Frequency of oscillation and varying mass
- Finding the ‘beam only’ frequency using Dunkerley’s Method
- Phase difference between displacement, its derivatives and measured acceleration
- Damped free and forced oscillations and damping coefficient
- Phase relationship between the applied force and beam position for different damping values
- Demonstration of a 2 degree of freedom (2DOF) system
- Demonstration of an undamped vibration absorber

### Essential Ancillary

- Versatile Data Acquisition System – bench-mounted version VDAS-B (mkII)

**Note:** This equipment needs VDAS® (mkII) and will not work with earlier versions of VDAS®. If unsure, contact TecQuipment or your local agent.

### Operating Conditions

*Operating environment:*

Laboratory environment

*Storage temperature range:*

–25°C to +55°C (when packed for transport)

*Operating temperature range:*

+5°C to +40°C

*Operating relative humidity range:*

80% at temperatures < 31°C decreasing linearly to 50% at 40°C

### Sound Levels

Less than 70 dB(A)

### Essential Services

*Bench space needed:*

650 mm x 2000 mm plus separate bench space for a suitable computer.

**Note:** For best experiment results, you must use this product on a strong, rigid bench.

*Electrical supply:*

Single-phase 90 VAC to 250 VAC 50 Hz to 60 Hz 1 A

### Specifications

*Nett dimensions and weight:*

1280 wide x 450 mm front to back x 800 mm high (assembled) and 80 kg

Other parts approximately 4 kg

*Approximate packed dimensions and weight:*

1 m<sup>3</sup> and 120 kg

*Other Parts Included*

- Storage tray and tools
- Spring for beam and spring tests
- Dashpot damper
- 1 Litre of non-toxic fluid (for dashpot damper)
- Vibration absorber
- 5 x 400 g masses



The TM1016 in use (other items not included)

- TecQuipment Ltd, Bonsall Street, Long Eaton, Nottingham NG10 2AN, UK
- **T** +44 115 972 2611 • **F** +44 115 973 1520 • **E** info@tecquipment.com • **W** www.tecquipment.com
- An ISO 9001 certified company
- VDAS is a registered trademark of TecQuipment Ltd

*tradition.*

*innovation.*

*integration.*

**infoWERK** is a leading expert in the development of eLearning courseware, learning system solutions, teaching and AV equipment.

**Furthermore infoWERK is the representative and system integrator of "TecQuipment".**

**TecQuipment** is one of the global leaders in technical teaching equipment for engineering. If you are interested in one of TecQuipment's products feel free to contact us at:



**infoWERK Medien & Technik GmbH**

**Martinsbühel 6 / A-6170 Zirl / Austria**

Phone: +43 (0) 5238 52099-0 / Fax: +43 (0) 5238 52099-40

E-Mail: [info@infowerk.at](mailto:info@infowerk.at) / Website: [infowerk.at](http://infowerk.at)

**Otto-Dürr-Straße 25**

**D-70435 Stuttgart, Zuffenhausen/ Germany**

Phone: +49 (0) 711 342471-0 / Fax: +49 (0) 711 342471-11

E-Mail: [info@de.infowerk.at](mailto:info@de.infowerk.at) / Website: [infowerk.at](http://infowerk.at)