



## Theory of Machines

# TM161

## Simple and Compound Pendulums

***Studies simple harmonic motion and the factors that affect the period of oscillation of pendulums.***



- One of a series of modular experiments that explore free vibrations in simple systems
- Quick, safe, and easy for students to use - needing minimal lab supervision
- Two modules - a simple pendulum and a compound pendulum for a range of experiments
- Integral scales to improve measurement accuracy
- The simple pendulum includes unique quick-change spheres and adjustable cord length to save time
- The compound pendulum includes extra parts to work as a Kater's pendulum
- Contains all parts needed for the experiments – including a stopwatch and tools

- TecEquipment Ltd, Bonsall Street, Long Eaton, Nottingham NG10 2AN, UK
- **T** +44 115 972 2611 • **F** +44 115 973 1520 • **E** info@tecquipment.com • **W** www.tecquipment.com
- An ISO 9001 certified company

# TM161

## Simple and Compound Pendulums

### Description

This product is part of a range that explores free vibrations in simple 'one degree of freedom' systems.

It introduces students to key scientific terms such as:

- Simple harmonic motion (SHM) and period of oscillation
- Mass moment of inertia
- Radius of gyration
- Routh's rule

This product fits to the sturdy Test Frame (TM160) for study or demonstration.

This product includes a simple pendulum and a compound pendulum. Both pendulums swing through small angles, showing the principles and use of simple harmonic motion using the small angle approximation.

The simple pendulum uses a cord which may be considered as 'light' so you can ignore its mass, leaving only the sphere and cord length as the important variables.

The compound or 'physical' pendulum uses a 'heavy' solid rod which has reasonable mass, so you must allow for it in theoretical equations.

Each pendulum has a back panel that fixes separately to the Test Frame. The back panel of each pendulum has an accurate scale and indicator, referenced to pendulum pivot or centre of mass points. This improves measurement accuracy - essential for good results.

The simple pendulum has a choice of two spheres suspended by a cord. An adjustable indicator also acts as the pendulum pivot point - allowing you to adjust the cord length in seconds. This can also provide a quick visual demonstration of the effect of cord length on period. Each sphere has a different mass for comparison and an internal spring retainer so you can easily swap them between experiments.

The compound pendulum has a solid rod that pivots on a hardened steel knife edge on the upper surface of a steel platform. This pendulum includes an additional spherical mass that fixes at any position along the rod. It also includes an extra pivot and disc-shaped mass so you can convert it for use as a Kater's pendulum.

The Kater's pendulum works as a reversible and adjustable compound pendulum. Students adjust the relative positions of its parts until they have equal time periods in both its standard and reversed arrangements. It then works as an accurate gravimeter.

Students test different pendulums to see how different factors, such as mass or pendulum length affect simple harmonic motion and the period of oscillation. The theory shows how to predict the period of oscillation of a given pendulum for comparison with actual results. It also shows how pendulums can produce an approximate value of the acceleration due to gravity.

### Standard Features

- Supplied with lecturer guide and student guide
- Five-year warranty
- Manufactured in accordance with the latest European Union directives

### Experiments

- Cord length and period of a simple pendulum.
- Mass and period of a simple pendulum.
- Using a simple pendulum to find the acceleration due to gravity.
- Centre of gravity and period of a compound pendulum.
- How an adjustable mass affects the period of a compound pendulum.
- Using a Kater's pendulum to find the acceleration due to gravity.



*The Simple Pendulum Module in use. Shown fitted to the Test Frame (TM160).*

- TecEquipment Ltd, Bonsall Street, Long Eaton, Nottingham NG10 2AN, UK
- **T** +44 115 972 2611 • **F** +44 115 973 1520 • **E** info@tecequipment.com • **W** www.tecequipment.com
- An ISO 9001 certified company

# TM161

## Simple and Compound Pendulums

### Operating Conditions

*Operating environment:*

Laboratory environment

*Storage temperature range:*

-25°C to +55°C (when packed for transport)

*Operating temperature range:*

+5°C to +40°C

*Operating relative humidity range:*

80% at temperatures < 31°C decreasing linearly to 50% at 40°C

### Essential Base Unit

Free Vibrations Test Frame (TM160)

### Specifications

*Nett dimensions and weight:*

*(Assembled)*

2 x 580 mm high x 220 mm wide x 100 mm front to back

10 kg total

*Approximate packed volume and weight:*

0.1 m<sup>3</sup> and 15 kg

*Other parts included:*

- Hexagon Tool
- Stopwatch
- Rule
- 2 x simple pendulum spheres of different mass

*tradition.*

*innovation.*

*integration.*

**infoWERK** is a leading expert in the development of eLearning courseware, learning system solutions, teaching and AV equipment.

**Furthermore infoWERK is the representative and system integrator of "TecQuipment".**

**TecQuipment** is one of the global leaders in technical teaching equipment for engineering. If you are interested in one of TecQuipment's products feel free to contact us at:



**infoWERK Medien & Technik GmbH**

**Martinsbühel 6 / A-6170 Zirl / Austria**

Phone: +43 (0) 5238 52099-0 / Fax: +43 (0) 5238 52099-40

E-Mail: [info@infowerk.at](mailto:info@infowerk.at) / Website: [infowerk.at](http://infowerk.at)

**Otto-Dürr-Straße 25**

**D-70435 Stuttgart, Zuffenhausen/ Germany**

Phone: +49 (0) 711 342471-0 / Fax: +49 (0) 711 342471-11

E-Mail: [info@de.infowerk.at](mailto:info@de.infowerk.at) / Website: [infowerk.at](http://infowerk.at)